JALMARS
00J0246

TRIFTANE
Excellence

ASSEMBLÉ EN FRANCE

S3 HRO FO SR
EN ISO 20345:2022
36 to 47

PUR
PLEINE FLEUR



- **Full grain leather**
- **Triftane™ Vibram Sole**
- **Toecap and antiperforation rustproof steel**
- **Antistatic**

- Black all purpose sporty ankle boots.
- Water-repellent full-grain leather upper. Thickness 1.9/2.1mm. Minimal stitching for increased watertightness and resistance to spilled and splashed liquids.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- "3D" inner lining, combining foam for comfort and protection and an open structure (mesh panel) that improves air flow around the foot.
- Lace up on five pairs of stainless steel triangles with leather bellows tongue for superior waterproofing. Black / red laces :100 cm.
- Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- Counter to maintain a snug-fitting heel.
- Initial hygiene layer covering the whole surface of the foot, removable, antistatic, antibacterially treated, anatomical and with heel schock absorbers. Capability of absorbing and removing high levels of perspiration.
- Stainless steel midsole.
- Patented 200 Joules safety toe cap with perforations, 9th width.

- **TRIFTANE™ VIBRAM** sole **technology** with a high adherence coefficient. Versatility of use. New formulation for increased durability.
  - Better mechanical resistance to abrasion, peeling and tearing.
  - NBR shore hardness : 60
  - Optimum grip level.
  - Hyperfunctional studs.
  - Heel shock absorbtion 28 Joules
  - Hollow heel, the hollowed out centre area makes wearers feel lighter as they walk.
  - Softane™ comfort layer, density 0.45
  - Resistant to oils and hydrocarbons, and acids and bases at low concentrations.
  - Resistant to direct contact heat up to 300°C.

Slip resistance tests results EN Standard ISO 20345:**2022**

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)
A- Heel to the front **0,44** (≥ 0,31)
B- Front to back **0,39** (≥ 0,36)

Additionnal requirement **SR :** Ceramic /Glycerin

C - Heel to the front **0,23** (≥ 0,19)
D- Front to back **0,26** (≥ 0,22)



Weight	Gross weight (42) : 1510 g / Net weight (42) : 1240 g			
Size	36 to 39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	365 x 260 x 133
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	695 x 276 x 385

Non contractual
Copyright JALLATTE
Limited distribution

09/10/2025

Jallatte®
www.jallatte.com